Ergo Mat Continuous Layout | Easy Cleaning

Natural rubber is used in producing standard mats to import excellent flexibility and durability.Other compounding ingredients have been specially selected and incorporated to optimize technical properties that are required for high-level performance in use. Stringent quality measures are adhered to in processing and molding of these products to satisfy the customer need. No bad smell & hazardous effect. Resistant to break oil and poorly resistant to most of other petroleum oils.

Features

- Extremely comfortable due to matrix design with buoyant air pockets for added fatigue relief and good grip.
- > Enhances worker productivity.
- > Diamond checkered plate design specially engineered for excellent grip.
- > Jig-saw puzzle ends and centers to create long runners.

AAG ERGO MAT

technical data sheet

- > Will not zip apart while in use but can easily be unlocked as needed.
- > Triangular pieces to make semi-circles or 45 degree circles.
- Colors to give visibility and safety.

Properties	Standard No	Value
1.Tensile Strength/Mpa	ASTM D412	3+/-1
2.Elongation @ Break%	ASTM D412	200+/-50
3. Hardness (shore A)	ASTM D2240	55+/-5
4. Specific gravity	ASTM D 1298	1.4+/-0.5
5. Tear Strength/Nmm-1	ASTM D624	20+/-5
6. Heat resistant	ASTM D573 70 h at 70°C	No visual damage

Product Details	Comment
Size of the Mat	71cm*79cm*13mm +/- 0.5
Colour	Black
Available Finish	Smooth tile with diamond surface





63 15/102020