

safety data sheet

58 11/02 2020

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

AAG Rubber Seal

Product no.

REACH registration number

Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Construction adhesive for most building applications

Uses advised against

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Aalborg Gummivarefabrik AS

Sundsholmen 3

9400 Nørresundby

Contact person

E-mail

info@aag.world

SDS date

2020-02-07

SDS Version

10.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Not classified according to Regulation (EC) No. 1272/2008 (CLP)

2.2. Label elements

Hazard pictogram(s)

Not applicable

Signal word

Hazard statement(s)

Not applicable

Precautionary statements

General Prevention Response Storage Disposal -

Identity of the substances primarily responsible for the major health hazards

Not applicable

AAG Rubber Seal



safety data sheet

11/02 2020

According to EC-Regulation 2015/830

▼Additional labelling

Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine. May produce an allergic reaction. (EUH208). Safety data sheet available on request. (EUH210)

Unique formula identifier (UFI)

2.3. Other hazards

Not applicable

Additional warnings

Not applicable

VOC (volatile organic compound)

VOC-Max: 60 g/l, MAXIMUM VOC CONTENT (-): (g/l (*)) g/l.

SECTION 3: Composition/information on ingredients

▼3.1/3.2. Substances/Mixtures

NAMF: Trimethoxyvinylsilane

IDENTIFICATION NOS.: CAS-no: 2768-02-7 EC-no: 220-449-8 REACH-no: 01-2119513215-52-XXXX

CONTENT:

CLP CLASSIFICATION: Flam. Liq. 3, Acute Tox. 4

H226, H332

N-(3-(trimethoxysilyl)propyl)ethylenediamine **IDENTIFICATION NOS.:** CAS-no: 1760-24-3 EC-no: 217-164-6 CONTENT: 0.1 - < 0.25%

CLP CLASSIFICATION: Skin Sens. 1B, Eye Dam. 1, STOT SE 3

H317, H318, H335

(*) See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

ATEmix(inhale, vapour) > 20 ATEmix(inhale, dust/mist) > 5 ATEmix(inhale, gas) > 20000 ATEmix(dermal) > 2000 ATEmix(oral) > 2000

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. The doctor can contact The National Poisons Information Service: Dial 0344 892 0111 (24 h service). Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Bring the person into fresh air and stay with him/her.

Skin contact

Wash contaminated skin with water.

Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 15 minutes. Seek medical assistance and continue flushing during transport.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Not applicable

4.2. Most important symptoms and effects, both acute and delayed

Under normal circumstances no known risks. This product contains substances that may trigger an allergic

AAG Rubber Seal

ado

safety data sheet

58 11/02 2020

According to EC-Regulation 2015/830

reaction to predisposed persons.

Symptoms may include reddening of the skin and rash, which typically occur after 12-72 hours.

4.3. Indication of any immediate medical attention and special treatment needed

Nothing special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous catabolic substances are produced. These are: Nitrogen oxides. Carbon oxides. Some metal oxides. Fire will result in dense black smoke. Exposure to combustion products may harm your health. Fire fighters should wear appropriate protection equipment. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No specific requirements.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. To the extent possible cleaning is performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section on "Disposal considerations" in regard of handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original container.

Storage temperature

No data available.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OFI

Methanol (released in small quantities during vulcanisation) Long-term exposure limit (8-hour TWA reference period): 200 ppm | 266 mg/m 3 Short-term exposure limit (15-minute reference period): 250 ppm | 333 mg/m 3 Comments: Sk (Sk = Can be absorbed through skin.)

VDNEL / PNEC

DNEL (Methanol (released in small quantities during vulcanisation)): 260 Exposure: Inhalation

AAG Rubber Seal

safety data sheet

According to EC-Regulation 2015/830

11/02 2020

8.2. Exposure controls

Compliance with the accepted occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, eating and drinking are not allowed in the work premises

Exposure scenarios

In the event exposure scenarios are appended to the safety data sheet, the operational conditions and risk management measures in these shall be complied with.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Airborne gas and dust concentrations must be kept at a minimum and below current limit values (see above). Installation of an exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure emergency eyewash and -showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Use only CE marked protective equipment.

Respiratory Equipment

Not relevant if the room is well ventilated. If used in small and very badly ventilated rooms a respirator may be used. In this case an AX-filter is recommended.

Skin protection

Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester.

▼Hand protection

Nitrile rubber

Material thickness: 0,1 mm.

Breakthrough time: > 480 minutes (Class 6)

Eye protection

No specific requirements.

SECTION 9: Physical and chemical properties

▼9.1. Information on basic physical and chemical properties

Pasta Form Colour Black

Odour No data available. Odour threshold (ppm) No data available. No data available. Viscosity (40°C) No data available.

Density (g/cm³) 1,46

Phase changes No data available. Melting point (°C) Boiling point (°C) No data available. Vapour pressure No data available. Decomposition temperature (°C) No data available. Evaporation rate (n-butylacetate = 100) No data available.

Data on fire and explosion hazards

AAG Rubber Seal

669

safety data sheet

According to EC-Regulation 2015/830

11/02 2020

Flash point (°C)
Ignition (°C)
Auto flammability (°C)
Explosion limits (% v/v)
Explosive properties
Solubility

Solubility in water n-octanol/water coefficient

9.2. Other information Solubility in fat (g/L)

No data available. No data available. No data available. No data available. No data available.

Insoluble No data available.

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section "Handling and storage".

10.3. Possibility of hazardous reactions

Nothing special

10.4. Conditions to avoid

Nothing special

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance: Trimethoxyvinylsilane Species: Rat Test: LD50 Route of exposure: Oral Result: 7100 mg/kg

Result: 7100 mg/kg

Substance: Trimethoxyvinylsilane

Species: Rabbit Test: LD50

Route of exposure: Dermal Result: 3200 mg/kg

Substance: Trimethoxyvinylsilane

Species: Rat Test: LD50

Route of exposure: Inhalation

Result: 16,8 mg/l/4h

Skin corrosion/irritation

Data on substance: Trimethoxyvinylsilane

Organism: Rabbit Duration of Exposure: 96 h Result: Not irritating

Serious eye damage/irritation

Data on substance: Trimethoxyvinylsilane

Organism: Rabbit Result: Irritating

Respiratory or skin sensitisation

Data on substance: Trimethoxyvinylsilane

Organism: Guinea pig

Result: Not sensitisingUnder normal circumstances no known risks. This product contains substances that may trigger an allergic reaction to predisposed persons.

AAG Rubber Seal

age

safety data sheet

58 11/02 2020

According to EC-Regulation 2015/830

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

Nothing special

SECTION 12: Ecological information

12.1. Toxicity

Substance: Trimethoxyvinylsilane

Species: Fish Test: LC50 Duration: 96 h Result: 191 mg/l

Substance: Trimethoxyvinylsilane

Species: Daphnia Test: EC50 Duration: 48 h Result: 169 mg/l

Substance: Trimethoxyvinylsilane

Species: Daphnia Test: NOEC Duration: 21 d Result: 25 mg/l

Substance: Trimethoxyvinylsilane

Species: Algae Test: NOEC Duration: 72 h Result: 25 mg/l

12.2. Persistence and degradability

SubstanceBiodegradabilityTestResultTrimethoxyvinylsilaneNoNo data availableNo data available

12.3. Bioaccumulative potential

Substance Potential bioaccumulation LogPow BCF

No data available.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

▼ 12.6. Other adverse effects

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is not covered by regulations on dangerous waste.

Waste

EWC code 08 04 10 Specific labelling

waste adhesives and sealants other than those mentioned in 08 04 09

AAG Rubber Seal



safety data sheet

According to EC-Regulation 2015/830

11/02 2020

Not applicable

Contaminated packing

No specific requirements.

SECTION 14: Transport information

14.1 - 14.4

Not dangerous goods according to ADR, IATA and IMDG.

ADR/RID

14.1. UN number
14.2. UN proper shipping name
14.3. Transport hazard
class(es)
14.4. Packing group
Notes
Tunnel restriction code

IMDG

UN-no.
Proper Shipping Name
Class
PG*
EmS
MP**
Hazardous constituent

IATA/ICAO

UN-no. Proper Shipping Name Class PG* -

14.5. Environmental hazards

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

- (*) Packing group
- (**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

Additional information

Not applicable

Seveso

Seveso III Part 2: Methanol (released in small quantities during vulcanisation), Methanol

Biocidal reg. no.

Not applicable

Sources

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and

AAG Rubber Seal

safety data sheet

11/02 2020

According to EC-Regulation 2015/830

health at work of pregnant workers and workers who have recently given birth or are breastfeeding. Directive 2004/42/CE of the European Parliament and of the Council of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677. The Stationery Office,

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (CLP). Regulation (EC) 1907/2006 (REACH).

The Control of Major Accident Hazards (COMAH) Regulations 2015.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H226 - Flammable liquid and vapour.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H332 - Harmful if inhaled.

H335 - May cause respiratory irritation.

The full text of identified uses as mentioned in section 1

Additional label elements

Not applicable

Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The safety data sheet is validated by

Robert Pedersen Date of last essential change

(First cipher in SDS version) 2018-12-14(9.0) Date of last minor change

(Last cipher in SDS version)

2019-11-19

ALPHAOMEGA. Licens nr.:3815228566, 7.0.0.0 www.chymeia.com