

AAG NARROW GROOVES



datasheet mat 3 mm

STANDARD MATTING

FEATURES

Non-slip surface.
Ribbed profiles.

ADVANTAGES

- Non-slippery
- Thermal and acoustic insulation
- Noise, vibration, and cold propagation reduction

BENEFITS

- Safety
- Comfort
- Economy

APPLICATIONS

Cutting pieces for vehicles step treads, shelves, or racks covers.


Cutting plates for protection of walls, columns, staircases, step stools, car trunks or vessels corridors.

Indoor installations.


MECHANICAL, PHYSICAL AND CHEMICAL PROPERTIES

	Measured characteristics	Standard	Value
MECHANICAL			
	Rubber compound		SBR
	Hardness	ASTM D2240	70 ± 5 Shore A
	Abrasion resistance (5 N)	ISO 4649	≤ 250 mm ³

PROFILE



Fine triangular ribbed (MT)



Rectangular ribbed (MR)



Wide ribbed (MG)

DIMENSIONS

Colour	Thickness (mm)	Width (mm)	Length (m)	Weight (kg/m ²)	Pattern
●	3 ± 0.3	1000 ± 2 %	10 ± 2 %	3.6	MT
●	3 ± 0.3	1200 ± 2 %	10 ± 2 %	3.6	MT
●	2.5 ± 0.3	1500 ± 2 %	15 ± 2 %	3.3	MR
●	5.8 ± 0.5	1000 ± 2 %	10 ± 2 %	6.9	MG
●	5.8 ± 0.5	1200 ± 2 %	10 ± 2 %	6.9	MG

IDENTIFICATION

Branding	Without.
Back face	Fabric impression.
Packaging	Rolled on cardboard tube Ø 80 mm.
Wrapping	Black polyethylene film.
Labelling	Self-adhesive label indicating product name, dimensions, area in m ² , nominal weight, and product code to allow product traceability.